



DEPARTMENT OF REGULATORY AND ECONOMIC RESOURCES (RER)
BOARD AND CODE ADMINISTRATION DIVISION

MIAMI-DADE COUNTY
PRODUCT CONTROL SECTION
11805 SW 26 Street, Room 208
Miami, Florida 33175-2474
T (786) 315-2590 F (786) 315-2599
www.miamidade.gov/economy

NOTICE OF ACCEPTANCE (NOA)

Waldun Forest Products Partnership
9393 287th Avenue
Maple Ridge, British Columbia V2W 1L1
Canada

SCOPE:

This NOA is being issued under the applicable rules and regulations governing the use of construction materials. The documentation submitted has been reviewed and accepted by Miami-Dade County RER - Product Control Section to be used in Miami Dade County and other areas where allowed by the Authority Having Jurisdiction (AHJ).

This NOA shall not be valid after the expiration date stated below. The Miami-Dade County Product Control Section (In Miami Dade County) and/or the AHJ (in areas other than Miami Dade County) reserve the right to have this product or material tested for quality assurance purposes. If this product or material fails to perform in the accepted manner, the manufacturer will incur the expense of such testing and the AHJ may immediately revoke, modify, or suspend the use of such product or material within their jurisdiction. RER reserves the right to revoke this acceptance, if it is determined by Miami-Dade County Product Control Section that this product or material fails to meet the requirements of the applicable building code.

This product is approved as described herein, and has been designed to comply with the Florida Building Code including the High Velocity Hurricane Zone of the Florida Building Code.

DESCRIPTION: Cedar Shakes & Shingles

LABELING: Each unit shall bear a permanent label with the manufacturer's name or logo, city, state and following statement: "Miami-Dade County Product Control Approved", unless otherwise noted herein.

RENEWAL of this NOA shall be considered after a renewal application has been filed and there has been no change in the applicable building code negatively affecting the performance of this product.

TERMINATION of this NOA will occur after the expiration date or if there has been a revision or change in the materials, use, and/or manufacture of the product or process. Misuse of this NOA as an endorsement of any product, for sales, advertising or any other purposes shall automatically terminate this NOA. Failure to comply with any section of this NOA shall be cause for termination and removal of NOA.

ADVERTISEMENT: The NOA number preceded by the words Miami-Dade County, Florida, and followed by the expiration date may be displayed in advertising literature. If any portion of the NOA is displayed, then it shall be done in its entirety.

INSPECTION: A copy of this entire NOA shall be provided to the user by the manufacturer or its distributors and shall be available for inspection at the job site at the request of the Building Official.

This renews NOA# 07-1113.05 and consists of pages 1 through 4.
The submitted documentation was reviewed by Alex Tigera.



NOA No.: 12-1203.09
Expiration Date: 02/20/18
Approval Date: 02/07/13
Page 1 of 4

ROOFING ASSEMBLY APPROVAL

Category:	Roofing
Sub-Category:	Wood Shingles and Shakes
Materials	Wood
Deck Type:	Wood

SCOPE

This approves roofing system using wood shingles and shakes as manufactured by Waldun Forest Products Partnership; a member of the Cedar Shake and Shingle Bureau Association and as described in Section 2 of this Notice of Acceptance, designed to comply with the Florida Building Code, high Velocity Hurricane Zone.

PRODUCT DESCRIPTION

<u>Product</u>	<u>Dimensions</u>	<u>Test Specifications</u>	<u>Product Description</u>
Certigrade Shingles (Grade 1)	Length 16", 18" Width 4 to 4 to 11"	Red Cedar sawn shingles and Hip and Ridge from clear heart wood: 100% edge grain, no defects	Certigrade Shingles (Grade 1)
Certi-Last Shingles (Grade 1)	Length 16", 18" Width 4 to 4 to 11"	Preservative treated Red Cedar sawn shingles made from Certigrade shingles	Certi-Last Shingles (Grade 1)
Certi-Cut (Grade 1)	Length 16", 18" Various	Red Cedar sawn shingles made from Certigrade shingles	Certi-Cut (Grade 1)
Certi-Guard (Grade 1)	Length 16", 18" Width 4 to 4 to 11"	Fire-retardant treated Red Cedar sawn shingles made from Certigrade shingles	Certi-Guard (Grade 1)
Certi-Split (Grade 1)	Length 15", 18", & 24" Width 4 to 4 to 11"	Handsplit and Resawn Shakes and Hip and Ridge from clear heart wood: 20% maximum flat grain	Certi-Split (Grade 1)
Certi-Guard (Grade 1)	Length 15", 18", & 24" Width 4 to 4 to 11"	Fire-retardant treated Red Cedar shakes made from Certi-Split shakes	Certi-Guard (Grade 1)
Certi-Last (Grade 1)	Length 15", 18", & 24" Width 4 to 4 to 11"	Preservative treated Red Cedar shakes made from Certi-Split shakes	Certi-Last (Grade 1)
Certi-groove (Grade 1)	Length 15", 18", & 24" Width 4 to 4 to 11"	Machine grooved shakes made from Certi-Split shakes	Certi-groove (Grade 1)
Certi-Sawn (Grade 1)	Length 15", 18", & 24" Width 4 to 4 to 11"	Taper Sawn Cedar Shakes, 100% clear face with a maximum 10% flat grain.	Certi-Sawn (Grade 1)



MANUFACTURING LOCATION

1. Maple Ridge, BC

EVIDENCE SUBMITTED

<u>Test Agency</u>	<u>Test Identifier</u>	<u>Test Name/Report</u>	<u>Date</u>
PRI Construction Materials	TAS 100-95	CSSB-002-02-04	03/02/07
PRI Construction Materials	TAS 100-95	CSSB-001-02-04	03/02/07
PRI Construction Materials		Fastener Pull-Through Resistance Test	

LIMITATIONS

1. Fire classification is not part of this acceptance; refer to a current Approved Roofing Materials Directory for fire ratings of this product.
2. Shall not be installed on roof mean heights in excess of 33 ft.
3. This acceptance is for wood deck applications. Minimum deck requirements shall be in compliance with applicable Building Code
4. Cedar Shake and Shingle bureau members shall have a quality control testing program by an approved independent listing agency having unannounced follow up visit. Follow up test results shall be made available to Miami Dade Product Control upon request.
5. All products listed herein shall have a quality assurance audit in accordance with the Florida Building Code and Rule 9N-3 of the Florida Administrative Code.

INSTALLATION

1. Waldun Forest Products Partnership Shakes and Shingle and its components shall be installed in strict compliance with Roofing Application Standard 130.

Fastener Pull Through Resistance	
<u>Description</u>	<u>Maximum Pull Force (lbs)</u>
Red Cedar Shingles 18"	119
Red Cedar Shakes 24"	134
1. Maximum thickness of 1/4"	

LABELING

1. Shingle/Shake Bundles shall be labeled with the Miami-Dade Seal as seen below, or the wording "Miami-Dade County Product Control Approved".



BUILDING PERMIT REQUIREMENTS

1. Application for building permit shall be accompanied by copies of the following:
 - 1.1 This Notice of Acceptance.
 - 1.2 Any other documents required by the Building Official or the applicable code in order to properly evaluate the installation of this system.

END OF THIS ACCEPTANCE



NOA No.: 12-1203.09
Expiration Date: 02/20/18
Approval Date: 02/07/13
Page 4 of 4