



DEPARTMENT OF REGULATORY AND ECONOMIC RESOURCES (RER)  
BOARD AND CODE ADMINISTRATION DIVISION

**NOTICE OF ACCEPTANCE (NOA)**

MIAMI-DADE COUNTY  
PRODUCT CONTROL SECTION  
11805 SW 26 Street, Room 208  
Miami, Florida 33175-2474  
T (786) 315-2590 F (786) 315-2599

[www.miamidade.gov/economy](http://www.miamidade.gov/economy)

**Inland Coating Corporation**

**P. O. Box 247  
Adel, IA 50003-0247**

**SCOPE:**

This NOA is being issued under the applicable rules and regulations governing the use of construction materials. The documentation submitted has been reviewed and accepted by Miami-Dade County RER - Product Control Section to be used in Miami Dade County and other areas where allowed by the Authority Having Jurisdiction (AHJ).

This NOA shall not be valid after the expiration date stated below. The Miami-Dade County Product Control Section (in Miami-Dade County) and/or the AHJ (in areas other than Miami-Dade County) reserve the right to have this product or material tested for quality assurance purposes. If this product or material fails to perform in the accepted manner, the manufacturer will incur the expense of such testing and the AHJ may immediately revoke, modify, or suspend the use of such product or material within their jurisdiction. RER reserves the right to revoke this acceptance, if it is determined by Miami-Dade County Product Control Section that this product or material fails to meet the requirements of the applicable building code.

This product is approved as described herein, and has been designed to comply with the Florida Building Code including the High Velocity Hurricane Zone of the Florida Building Code.

**DESCRIPTION: RC 2000 Rubber Roof Coating System**

**LABELING:** Each unit shall bear a permanent label with the manufacturer's name or logo, city, state and following statement: "Miami-Dade County Product Control Approved", unless otherwise noted herein.

**RENEWAL** of this NOA shall be considered after a renewal application has been filed and there has been no change in the applicable building code negatively affecting the performance of this product.

**TERMINATION** of this NOA will occur after the expiration date or if there has been a revision or change in the materials, use, and/or manufacture of the product or process. Misuse of this NOA as an endorsement of any product, for sales, advertising or any other purposes shall automatically terminate this NOA. Failure to comply with any section of this NOA shall be cause for termination and removal of NOA.

**ADVERTISEMENT:** The NOA number preceded by the words Miami-Dade County, Florida, and followed by the expiration date may be displayed in advertising literature. If any portion of the NOA is displayed, then it shall be done in its entirety.

**INSPECTION:** A copy of this entire NOA shall be provided to the user by the manufacturer or its distributors and shall be available for inspection at the job site at the request of the Building Official.

This NOA renews NOA No. 16-0811.05 and consists of pages 1 through 4.

The submitted documentation was reviewed by *Freddy Semino*



NOA No.: 17-0615.06  
Expiration Date: 11/02/22  
Approval Date: 08/03/17  
Page 1 of 4

## ROOFING COMPONENT APPROVAL

**Category:** Roofing  
**Sub-Category:** Cement-Adhesive-Coatings  
**Material:** SEBS Elastomeric  
**Fire Classification:** See Limitation #1

### SCOPE:

This approves “**RC 2000 Rubber Roof Coating System**” as a roof maintenance coating system, as manufactured by Inland Coatings Corporation. This product is approved as described in this Notice of Acceptance and is designed to comply with the Florida Building Code and the High Velocity Hurricane Zones of the Florida Building Code.

### PRODUCT DESCRIPTION:

<u>Manufactured by Applicant</u>	<u>Dimensions</u>	<u>Test Specifications</u>	<u>Product Description</u>
RC 2000 Rubber Roof Coating	1, 5 & 55 gallons	ASTM D 6083 ASTM D 903 Fed. Spec. TTC-555B	A single component, solvent based (SEBS) elastomeric industrial maintenance coating.
DF 1000 Rubber Deck Filler	1, 5 & 55 gallons	Proprietary	A single component, solvent based (SEBS) elastomeric industrial maintenance coating. If this product is installed in areas exposed to weather then it must be top coated with RC 2000 Roof coating.
RC 2200 Rubber Seam Compound	1, 5 & 55 gallons	Proprietary	A single component, solvent based (SEBS) elastomeric industrial maintenance coating. If this product is installed in areas exposed to weather then it must be top coated with RC 2000 Roof coating.

### MANUFACTURING LOCATION:

1. Adel, IA.

### EVIDENCE SUBMITTED:

<u>Test Agency</u>	<u>Test Identifier</u>	<u>Test Name/Report</u>	<u>Date</u>
PRI Asphalt Technologies	ICCN-011-02-01	ASTM D 6083 ASTM D 903 Fed. Spec. TTC-555B	05/31/17



## INSTALLATION:

**System Components:** RC 2000 Rubber Roof Coating  
DF 1000 Rubber Deck Filler  
RC 2200 Rubber Seam Compound

**Thickness:** See system specifications below.

**Specifications:** ASTM D 6083, ASTM D 903

**Preparation:** The surface shall be clean, sound and dry prior to application. All surface preparation, application methods and application rates shall be in compliance with the coating manufacturer's published application instructions and current Miami-Dade County Product Control Notice of Acceptance.

**Description:** A single component, solvent based (SEBS) elastomeric industrial maintenance coating for use on various roof decks.

- System Specifications**
- **Metal Roofs:** Prime any corroded areas with RC 2000 at an application rate of 1.0 gal/100 ft<sup>2</sup>. Seams shall be coated with RC 2200 Rubber Seam Compound as needed. Allow adequate dry time between coats. A minimum of one finish coat of RC 2000 Rubber Roof Coating applied by brush, roller or spray at an application rate of 1.0 gal/100 ft<sup>2</sup>.
  - **Modified Bitumen SBS and APP roofing:** Prime with a coat of DF 1000 Rubber Deck Filler at an application rate of 1.5 gal/ 100 ft<sup>2</sup>. Apply a minimum of one finish coat of RC 2000 Rubber Roof Coating applied by brush, roller or spray at a rate of 1.0 gal/ 100 ft<sup>2</sup>.
  - **Smooth surface BUR:** Prime with a coat of DF 1000 Rubber Deck Filler at an application rate of 1.5 gal/100 ft<sup>2</sup>. Apply a minimum of one finish coat of RC 2000 Rubber Roof Coating applied by brush, roller or spray at a rate of 1.0 gal/ 100 ft<sup>2</sup>.
  - **EPDM & TPO Single Ply Roof Systems:** Apply a flash coat of RC 2000 Rubber Roof Coating applied by brush, roller or spray at an application rate of .75 gal/ 100 ft<sup>2</sup>. Allow surface to dry thoroughly. Seams shall be coated with RC 2200 Rubber Seam Compound as needed. Apply a minimum of one finish coat of RC 2000 Rubber Roof Coating by brush, roller or spray at an application rate of 1.0 gal/ 100 ft<sup>2</sup>.
  - **Hypalon Single Ply Roof Systems:** Seams shall be coated with RC 2200 Rubber Seam Compound as needed. Apply a minimum of one finish coat of RC 2000 Rubber Roof Coating applied by brush, roller or spray at an application rate of 1.25 gal/ 100 ft<sup>2</sup>.
  - **Spray Polyurethane Foam (SPUF) Roof Systems:** Apply a minimum of one finish coat of RC 2000 Rubber Roof Coating applied by brush, roller or spray at an application rate of 1.5 gal/ 100 ft<sup>2</sup>.



## **LIMITATIONS:**

1. Fire classification is not part of this acceptance; refer to a current Approved Roofing Materials Directory for fire rating of this product.
2. RC 2000 Rubber Roof Coating System shall not be applied in inclement weather conditions.
3. The products listed herein are components of roof assemblies and are approved for use with roof assemblies that list any of the products listed herein as part of their roof assemblies Notice of Acceptance.
4. All products listed herein shall have an unannounced follow-up quality control program from an approved listing agency. Follow up test results shall be made available to Miami-Dade County Product Control upon request.
5. All approved products listed herein shall be labeled in compliance with TAS 121 and shall bear the imprint or identifiable marking of the manufacturer's name or logo and following statement: "Miami-Dade County Product Control Approved" or the Miami-Dade County Product Control Seal as shown below.



6. Change in materials, use, or manufacture of any of the products listed herein shall be cause for termination of this Notice of Acceptance.
7. RC 2000 Rubber Roof Coating System shall be installed in accordance with manufacturer's Product Data Sheet.
8. RC 2000 Rubber Roof Coating System shall be used as a roof maintenance coating system in accordance with applicable Building Code. RC 2000 Rubber Roof Coating System is not approved to be used as a repair or recover system.
9. All products listed herein shall have a quality assurance audit in accordance with the Florida Building Code and Rule 61G20-3 of the Florida Administrative Code.
10. If DF 1000 Rubber Deck Filler or RC 2200 Rubber Seam Compound is installed in areas exposed to weather then it must be top coated with RC 2000 Roof coating as specified by manufacturer's published application instructions.

**END OF THIS ACCEPTANCE**

