



DEPARTMENT OF REGULATORY AND ECONOMIC RESOURCES (RER)  
BOARD AND CODE ADMINISTRATION DIVISION

**NOTICE OF ACCEPTANCE (NOA)**

MIAMI-DADE COUNTY  
PRODUCT CONTROL SECTION  
11805 SW 26 Street, Room 208  
Miami, Florida 33175-2474  
T (786) 315-2590 F (786) 315-2599  
[www.miamidade.gov/economy](http://www.miamidade.gov/economy)

**NaturaSeal Distribution Inc.**  
**960 Edgeley Blvd. Unit #4**  
**Vaughan, Ontario Canada L4K 4V4**

**SCOPE:**

This NOA is being issued under the applicable rules and regulations governing the use of construction materials. The documentation submitted has been reviewed and accepted by Miami-Dade County RER - Product Control Section to be used in Miami Dade County and other areas where allowed by the Authority Having Jurisdiction (AHJ).

This NOA shall not be valid after the expiration date stated below. The Miami-Dade County Product Control Section (in Miami-Dade County) and/or the AHJ (in areas other than Miami-Dade County) reserve the right to have this product or material tested for quality assurance purposes. If this product or material fails to perform in the accepted manner, the manufacturer will incur the expense of such testing and the AHJ may immediately revoke, modify, or suspend the use of such product or material within their jurisdiction. RER reserves the right to revoke this acceptance if it is determined by Miami-Dade County Product Control Section that this product or material fails to meet the requirements of the applicable building code.

This product is approved as described herein and has been designed to comply with the Florida Building Code including the High Velocity Hurricane Zone of the Florida Building Code.

**DESCRIPTION: Novaset R250 ISW**

**LABELING:** Each unit shall bear a permanent label with the manufacturer's name or logo, city, state and following statement: "Miami-Dade County Product Control Approved", unless otherwise noted herein.

**RENEWAL** of this NOA shall be considered after a renewal application has been filed and there has been no change in the applicable building code negatively affecting the performance of this product.

**TERMINATION** of this NOA will occur after the expiration date or if there has been a revision or change in the materials, use, and/or manufacture of the product or process. Misuse of this NOA as an endorsement of any product, for sales, advertising or any other purposes shall automatically terminate this NOA. Failure to comply with any section of this NOA shall be cause for termination and removal of NOA.

**ADVERTISEMENT:** The NOA number preceded by the words Miami-Dade County, Florida, and followed by the expiration date may be displayed in advertising literature. If any portion of the NOA is displayed, then it shall be done in its entirety.

**INSPECTION:** A copy of this entire NOA shall be provided to the user by the manufacturer or its distributors and shall be available for inspection at the job site at the request of the Building Official.

This NOA revises NOA# 24-0711.03 and consists of pages 1 through 4.  
The submitted documentation was reviewed by Alex Tigera.

01/02/25



NOA No.: 24-1114.03  
Expiration Date: 08/15/29  
Approval Date: 01/02/25  
Page 1 of 4

## ROOFING COMPONENT APPROVAL

**Category:** Roofing  
**Sub-Category:** Cements - Coatings - Adhesives  
**Materials:** Elastomeric

### SCOPE:

This approves **Novaset R250 ISW** roof maintenance coating system, as manufactured by **NaturaSeal Distribution Inc.** as described in this Notice of Acceptance, designed to comply with the Florida Building Code and the High Velocity Hurricane Zone of the Florida Building Code.

### MANUFACTURING LOCATIONS:

1. Vaughan, Ontario, Canada

### EVIDENCE SUBMITTED:

<u>Test Agency</u>	<u>Test Identifier</u>	<u>Test Name/Report</u>	<u>Date</u>
Intertek	Q4446.04-106-18 R1	ASTM D 6083	03/27/24
	R9275.01-106-18 R0	ASTM D 903	11/15/24



## PHYSICAL PROPERTIES OF COMPONENTS:

**Trade name:** Novaset R250 ISW  
**Thickness:** See description below.  
**Specifications:** ASTM D6083  
**Description:** Fluid-applied seamless roof membrane composed of an advanced engineered blend of thermo-active polymerized modified emulsion (PME) technology applied to the following substrates:

- **Galvanized Steel:** Apply one coat at a rate of 1 gal./30 ft<sup>2</sup> per coat to yield an average total thickness of 57 wet mils or 30 DFT or,  
one coat at a rate of 1 gal./25 ft<sup>2</sup> per coat to yield an average total thickness of 66 wet mils or 35 DFT or,  
one coat at a rate of 1 gal./40 ft<sup>2</sup> per coat to yield an average total thickness of 75 wet mils or 40 DFT.
- **Concrete\*:** Apply one coat at a rate of 1 gal./30 ft<sup>2</sup> per coat to yield an average total thickness of 57 wet mils or 30 DFT or,  
one coat at a rate of 1 gal./25 ft<sup>2</sup> per coat to yield an average total thickness of 66 wet mils or 35 DFT or,  
one coat at a rate of 1 gal./40 ft<sup>2</sup> per coat to yield an average total thickness of 75 wet mils or 40 DFT.
- **PVC:** Apply one coat at a rate of 1 gal./30 ft<sup>2</sup> per coat to yield an average total thickness of 57 wet mils or 30 DFT or,  
one coat at a rate of 1 gal./25 ft<sup>2</sup> per coat to yield an average total thickness of 66 wet mils or 35 DFT or,  
one coat at a rate of 1 gal./40 ft<sup>2</sup> per coat to yield an average total thickness of 75 wet mils or 40 DFT.
- **Modified Bitumen:** Apply one coat at a rate of 1 gal./30 ft<sup>2</sup> per coat to yield an average total thickness of 57 wet mils or 30 DFT or,  
one coat at a rate of 1 gal./25 ft<sup>2</sup> per coat to yield an average total thickness of 66 wet mils or 35 DFT or,  
one coat at a rate of 1 gal./40 ft<sup>2</sup> per coat to yield an average total thickness of 75 wet mils or 40 DFT.
- **TPO (Aged):** Apply one coat at a rate of 1 gal./30 ft<sup>2</sup> per coat to yield an average total thickness of 57 wet mils or 30 DFT or,  
one coat at a rate of 1 gal./25 ft<sup>2</sup> per coat to yield an average total thickness of 66 wet mils or 35 DFT or,  
one coat at a rate of 1 gal./40 ft<sup>2</sup> per coat to yield an average total thickness of 75 wet mils or 40 DFT.

\*Note: See Limitation #1

**Container Sizes:** 5 gallon pail, 55 gallon drum, or 264 gallon tote. Note cautions on container label.

**Systems Approvals:** Methods of application and quantities shall comply with the specific Roof Assembly System's Product Control Notice of Acceptance where it exceeds standards of this NOA.



NOA No.: 24-1114.03  
Expiration Date: 08/15/29  
Approval Date: 01/02/25  
Page 3 of 4

**BUILDING PERMIT REQUIREMENTS:**

Application for building permit shall be accompanied by copies of the following:

1. This Notice of Acceptance
2. Any other documents required by the building official or the Applicable Building Code in order to properly evaluate the installation of this system.

**LIMITATIONS:**

1. Novaset R250 ISW is not approved as and shall not be used as a Roof System or Waterproofing System as required by the Florida Building Code Chapter 15 HVHZ.
2. Fire classification is not part of this acceptance; refer to a current Approved Roofing Materials Directory for fire rating of this product.
3. Fire classification is not part of this acceptance; refer to a current Approved Roofing Materials Directory for fire rating of this product.
4. Novaset R250ISW shall not be applied in inclement weather conditions.
5. The product listed herein are components of roof assemblies and are approved for use with roof assemblies that list any of the products listed herein as part of their roof assemblies Notice of Acceptance. If a product is not listed as part of roof assemblies Notice of Acceptance, a request may be made to the local building official or the Miami Dade County Product Control Section for approval provided that appropriate documentation is provided.
6. Change in materials, use, or manufacture of any of the products listed herein shall be cause for termination of this Notice of Acceptance.
7. Novaset R250ISW shall be applied in accordance with manufacturer’s published application instructions.
8. All products listed herein shall have an unannounced follow-up quality control program from an approved listing agency. Follow up test results shall be made available to the Miami Dade Product Control upon request.
9. The use of a reinforcing fabric in a maintenance coating is only to enhance the coating’s ability to deliver efficient and long term performance through the protection of the underlying roof system and in this particular use does not become a roof system itself.
10. All products listed herein shall have a quality assurance audit in accordance with the Florida Building Code and Rule 61G20-3 of the Florida Administrative Code.
11. All approved products listed herein shall be labeled in compliance with TAS 121 and shall bear the imprint or identifiable marking of the manufacturer's name or logo, city and state of manufacturing facility, and the following statement: "Miami-Dade County Product Control Approved" or the Miami-Dade County Product Control Seal as shown below.



**END OF THIS ACCEPTANCE**

